

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 July 2006 (27.07.2006)

PCT

(10) International Publication Number
WO 2006/077472 A1

(51) International Patent Classification:
F02M 61/06 (2006.01) *F02M 45/02* (2006.01)

(21) International Application Number:
PCT/IB2005/051474

(22) International Filing Date: 5 May 2005 (05.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2005102000399 18 January 2005 (18.01.2005) CN
60/594,110 11 March 2005 (11.03.2005) US

(71) Applicant and

(72) Inventor: HOU, Deyang [CN/US]; 5111 Avondale Drive,
Sugar Land, TX 77479 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv))

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MIXED-MODE FUEL INJECTOR WITH A VARIABLE ORIFICE



(57) Abstract: The invention disclosed a mixed-mode fuel injector with micro-variable-circular-orifice (MVCO), which is a fuel injection device for internal combustion engines, either diesel or gasoline engines. The fuel injector is a high-accuracy couple of components comprising a needle valve (1) and a nozzle body (5). Said needle valve is movable back and forth and received in said nozzle body to provide an opening position for fuel injection and a biased closing position. Said nozzle body has multiple micro-channels (6) on the inner conical surface (C) close to the tip of the nozzle body. The injector has a MVCO (4) comprising a micro-variable-circular aperture and multiple-micro-channels, and has means of generating variable mixed-mode sprays of conical and multi jet shapes, with a major homogeneous conical spray at low to medium injection loads.

WO 2006/077472 A1